



### AB SERIES ARTICULATING BOOM LIFTS

#### **STANDARD FEATURES**

- AC electric drive
- Proportional controls
- ▶ Load sensing system
- ▶ All motion alarm
- ▶ Active tilt alarm
- ▶ Battery charge display
- ▶ 60A charger
- Non-marking tires
- ▶ 28 mph wind rating
- Drive at full height

- Outside/inside rated
- ▶ CAN communication protocol
- ▶ Hour meter
- Turntable rotation lock
- Lifting points
- ▶ Horn
- ▶ Electric brakes
- ▶ Emergency lowering system
- ▶ 2-year parts & labor warranty
- ▶ 5-year structural warranty

#### **STANDARDS COMPLIANCE**

NSI A92.20

# PRELIMINARY BROCHURE SUBJECT TO CHANGE

## AB-43JNe ARTICULATING BOOM

DIV	ENGLONG			
DIM	Working Height (2 Person Indoor/1 Person Outdoor)	48.7 ft	15 m	
	Platform Height (2 Person Indoor/1 Person Outdoor)	42.7 ft	13 m	
	Up and Over Height	21.5 ft	6.55 m	
	Horizontal Reach	28.4 ft	8.65 m	
A	Length	22.1 ft	6.75 m	
В	Width	5 ft	1.52 m	
С	Stowed Height	6.9 ft	2.1 m	
D	Transport Height	9.8 ft	3 m	
E	Jib Length	5.2 ft	1.58 m	
F	Transport Length	18.4 ft	5.6 m	
G	Wheelbase	78.7 in	2 m	
Н	Ground Clearance	8.3 in	0.21 m	
1	Platform Width	51.2 in	1.3 m	
J	Platform Length	35.4 in	0.9 m	
SPECIFICATIONS				
Rated Occupancy (Indoor/Outdoor)		2 / 1 Person(s)		
Platform Capacity		507 lbs	230 kg	
Turn Radius (Inside/Outside)		67 / 146 in	1.7 / 3.7 m	
Gradeability		25%	25%	
Horizontal Platform Rotation		180°		
Turntable Rotation 355°		jo		
Drive	e Speed Elevated	0.5 mph	0.8 km/h	
Drive Speed Lowered		2.8 mph	4.5 km/h	
Tires		22.4 x 9 in	57 x 23 cm	
Weight		15,873 lbs	7,200 kg	
POWER				
Battery		48V/400 Ah		
Hydr	aulic Tank	7.9 gal	30 L	





