



EL-4555Xe SCISSOR



EL SERIES

SELF-PROPELLED MOBILE ELEVATED WORK PLATFORM

STANDARD FEATURES

- ▶ Electric drive
- ▶ Proportional controls
- ▶ LeakGuard®
- ▶ 110V power-to-platform
- ▶ Indoor & outdoor operation settings
- ▶ 30A charger
- ▶ Non-slip deck
- ▶ All motion alarm
- ▶ Flashing beacon
- ▶ Removable platform controls
- ▶ Self-locking gate
- ▶ Lifiable with forklift or crane
- ▶ Dual maintenance bars
- ▶ Onboard diagnostic system
- ▶ Manual decent cable
- ▶ Active tilt alarm
- ▶ Slide out extension
- ▶ Automatic pothole protection
- ▶ Non-marking tires
- ▶ Horn
- ▶ CAN communication protocol
- ▶ 2-year parts & labor warranty
- ▶ 5-year structural warranty

STANDARDS COMPLIANCE

- ▶ ANSI A92.20

OPTIONS

- ▶ Perimeter Lights
- ▶ Telematics

EL SERIES

SPECIFICATIONS		EL-4555Xe
A	Working Height (2 Person Indoor)	51.1 ft 15.6 m
	Working Height (1 Person Outdoor)	38 ft 11.6 m
B	Platform Height Maximum (2 Person Indoor)	45.1 ft 13.75 m
	Platform Height Maximum (1 Person Outdoor)	32 ft 9.75 m
C	Platform Height Minimum	63 in 1.6 m
D	Ground Clearance Elevated	0.79 in 2 cm
E	Ground Clearance Lowered	4.7 in 12 cm
F	Overall Length w/Step	109.8 in 2.79 m
G	Overall Width	55 in 1.39 m
H	Stowed Height (Rails Unfolded)	103.9 in 2.64 m
	Stowed Height (Rails Folded)	83.5 in 2.12 m
I	Platform Length	105.5 in 2.68 m
J	Platform Width	45.3 in 1.15 m
K	Slide Out Extension Deck Length	39.4 in 1 m
	Wheelbase	87.4 in 2.22 m
	Tires	15 x 5 in 38 x 12.7 cm
PERFORMANCE		
	Rated Occupancy (Indoor/Outdoor)	2 / 1 Person(s)
	Platform Capacity	771.6 lbs 350 kg
	Slide Out Extension Deck Capacity	330.7 lbs 150 kg
	Gradeability	25%
	Inside Turn Radius	0 in 0 cm
	Drive Speed Elevated	0.4 mph 0.6 km/h
	Drive Speed Lowered	2.8 mph 4.5 km/h
	Working Slope	2° / 3°
	Lift Speed (Up/Down)	77 / 62 s
	Weight	8818 lbs 4000 kg
POWER		
	Hydraulic Tank Capacity	5.5 gal 20.7 L
	Battery	4 x 12V 300 Ah

