



VM-26Je VERTICAL MAST



VERTICAL MAST SERIES

SELF-PROPELLED MOBILE ELEVATED WORK PLATFORM

STANDARD FEATURES

- ▶ AC electric drive
- ▶ LeakGuard®
- ▶ Proportional controls
- ▶ Silent drive
- ▶ Zero tailswing
- ▶ Tool tray
- ▶ Drive at full height
- ▶ Motion alarm
- ▶ Onboard diagnostic display
- ▶ 30A charger
- ▶ Load sensing
- ▶ Overload alarm
- ▶ Tilt alarm
- ▶ Automatic battery water filling
- ▶ Non-marking tires
- ▶ Electric brake release
- ▶ Pothole protection
- ▶ Emergency lowering system
- ▶ CAN communication Protocol
- ▶ Crane lift point
- ▶ Hour meter
- ▶ Horn
- ▶ 2-year parts & labor warranty
- ▶ 5-year structural warranty

STANDARDS COMPLIANCE

- ▶ ANSI A92.20

PRELIMINARY BROCHURE
SUBJECT TO CHANGE

VM-26Je

VERTICAL MAST

DIMENSIONS

	Working Height	31.6 ft	9.8 m
A	Maximum Platform Height	25.6 ft	7.8 m
	Horizontal Reach	10.3 ft	3.15 m
B	Up and Over Clearance	21 ft	6.4 m
C	Stowed Height	6.5 ft	1.99 m
D	Stowed Length	8.8 ft	2.67 m
E	Chassis Length	5.6 ft	1.7 m
F	Width	3.3 ft	0.99 m
G	Platform Length	42.1 in	1.07 m
H	Platform Width	38.9 in	0.99 m
I	Ground Clearance Elevated	1.6 in	0.04 m
J	Ground Clearance Stowed	3.9 in	0.1 m
K	Wheelbase	47.2 in	1.2 m

SPECIFICATIONS

	2 / 1 Person(s)	
Occupants (Indoor/Outdoor)		
Platform Capacity	441 lbs	200 kg
Tailswing	0 in	0 m
Drive Speed Stowed	3.7 mph	6 km/h
Drive Speed Elevated	0.4 mph	0.65 km/h
Gradeability		25%
Jib Rotation		135°
Turntable Rotation		350°
Working Slope		2° / 3°
Tires	15.9 x 5 in	41 x 13 cm
Weight	6,173 lbs	2,800 kg

POWER

Hydraulic Tank Capacity	3.2 gal	12 L
Batteries	24V / 250A	

